



CANBUILT MFG.

Toll-Free in Canada: 1-888-607-2926 Phone: 416-749-6555 Fax: 416-749-7597
Email: sales@canbuilt.com Website: www.canbuilt.com

103 Milvan Drive,
Toronto, Ontario,
Canada, M9L 1Z7

AIR OPERATED DOUBLE DIAPHRAGM PUMP

These pumps are well suited for industrial or automotive applications. They feature an air distribution fully serviceable externally, through a fully bolted construction.



MODEL # DP-3500C



MODEL # DP-4000C

SPECIFICATIONS	MODEL DP-3500C	MODEL DP-4000C
Inlet/Outlet	3/4"	1"
Air inlet	1/4"	1/4"
Flow Rate	16 GPM/60 LPM	24 GPM/90 LPM
Max Air Inlet Pressure	115 PSI / 8Bar	115PSI / 8BAR
Max Outlet Pressure	115 PSI / 8Bar	115 PSI / 8Bar
Max Diameter Solid	1/8"	1/8"
Body Construction	Polypropylene	Aluminum
Membrane	Nitrile, Fluorin Rubber	
Fluid Compatibility	Diesel, Kerosene, Oils	

REQUIRED:
Filter / Regulator
Model # FLR-1559

1/4" Air line filter with water drain, regulator, gauge and ball valve .40 micron filter- 1/4" NPT Inlet / Outet. Regulate air flow for optimum pump efficiency. On/Off valve allows user to turn on or turn off the diaphragm pump.



3/4" Brass Y Strainer
Model # DP-3501YB

Strains the fluid from larger debris/particulates to protect the pump



3/4" Stainles Y Strainer
Model # DP-3500Y



QUALITY • PERFORMANCE • LONGEVITY