



# CANBUILT MFG.

Toll-Free in Canada: 1-888-607-2926 Phone: 416-749-6555 Fax: 416-749-7597  
Email: sales@canbuilt.com Website: www.canbuilt.com

103 Milvan Drive,  
Toronto, Ontario,  
Canada, M9L 1Z7

## MANUAL OIL CONTROL HANDLES

### Mechanical Control Handle Litre Meter Model # **LH-24792**

Very robust rotary-piston type Hose End Meter including swivel, valve handle, inlet strainer, outlet hose and non-drip nozzle.

Functions:

- Resetable trip meter
- Non-resetable 5 digit totaliser display
- No batteries required, environmental friendly
- Trigger can be locked in open position

Max flow	25 litres/min
Max Pressure	7 (70) MPa/Bar
Inlet thread	G1/2" (f)
Outlet	Hose 1/2" BSP



Spring loaded, non-drip tip

- Flow range 1-30 l/min (0,25-8 gpm)
- Max. working pressure 1,450 psi (100 bar)
- Operating temperature -45 °C a 70 °C (-50 °F to 160 °F)
- Accuracy  $\pm 0.65\%$
- Fluid viscosity range 50 - 50,000 cSt
- Inlet and outlet connections 1/2" BSP
- Compatible fluids Low to high viscosity lubricants, ATF and Antifreeze
- Wetted materials Aluminum, stainless steel, zinc alloy, NBR, zinc plated steel, brass.
- Totalizing register 5 digits (99,999 liters) - 5 digits (99,999 gallons)
- Weight 1 kg - 2.2 lb

*QUALITY • PERFORMANCE • LONGEVITY*